

8" Spacing

Order Code	Number of Blades		# of Bearings	Approx. Width	Approx. Transport Height	Approx. DBHP**	Weight
	Front	Rear					
TD500-82N	40	42	22	28' (8.5 m)	12' 4" (3.7 m)	126 - 168	13,100 lb (5,742 kg)
TD500-94N	46	48	24	32' (9.7 m)	14' 4" (4.4 m)	144 - 192	14,202 lb (6,442 kg)
TD500-106W	52	54	30	35' 6" (10.8 m)	16' 0" (4.9 m)	160 - 213	16,479 lb (7,475 kg)
TD500-114W	56	58	30	38' (11.6 m)	17' 2" (5.2 m)	171 - 228	17,077 lb (7,746 kg)
TD500-122W †	60	62	34	40' 6" (12.3 m)	18' 1" (5.5 m)	182 - 243	18,254 lb (8,280 kg)

9" Spacing

Order Code	Number of Blades		# of Bearings	Approx. Width	Approx. Transport Height	Approx. DBHP**	Weight
	Front	Rear					
TD500-78N	38	40	24	29' 6" (9.0 m)	13' 2" (4.0 m)	148 - 207	13,508 lb (6,140 kg)
TD500-86N	42	44	24	32' 6" (9.9 m)	14' 8" (4.5 m)	163 - 228	13,772 lb (6,247 kg)
TD500-94W	46	48	28	35' 6" (10.8 m)	16' 2" (4.9 m)	178 - 249	15,937 lb (7,229 kg)
TD500-102W	50	52	30	38' 6" (11.7 m)	17' 4" (5.3 m)	193 - 270	16,649 lb (7,552 kg)
TD500-106W †	52	54	30	40' (12.1 m)	17' 10" (5.4 m)	200 - 280	17,554 lb (7,962 kg)